

# 4150 CORE | Combi Tool

| Specifications                   |     |                 |
|----------------------------------|-----|-----------------|
| article number                   |     | 158.012.062     |
| model                            |     | 4150 CORE       |
| equipped with (connector type)   |     | CORE            |
| short description                |     | Combi Tool      |
| max. working pressure            | psi | 10443           |
| max. cutting opening             | in  | 9               |
| max. spreading force             | lbf | 47435           |
| pulling distance                 | in  | 16.4            |
| spreading distance               | in  | 14.2            |
| min. spreading force (EN 13204)  | lbf | 7868            |
| max. cutting force C0            | lbf | 85427           |
| max. squeezing force             | lbf | 17085           |
| max. pulling force               | lbf | 14388           |
| required oil content (effective) | oz  | 2.8             |
| weight, ready for use            | lb  | 31.1            |
| dimensions (LxWxH)               | in  | 31 x 9.3 x 7.5  |
| temperature range                | °F  | -4 + 131        |
| EN 13204 classification          |     | CK35/360-H-14.1 |
| NFPA 1936 compliant              |     | yes             |
| NFPA 1936, cutting capacity      |     | A7 B8 C6 D7 E7  |
| NFPA 1936, HPF                   | lbf | 14388           |
| NFPA 1936, LPF                   | lbf | 8318            |
| NFPA 1936, HSF                   | lbf | 7644            |
| NFPA 1936, LSF                   | lbf | 6519            |
| round bar (NFPA 1936)            | in  | 6               |

| Safety factors / tests           |  |
|----------------------------------|--|
| safety factor pigtail hoses      | 1:4  |
| hydraulic safety factor          | 2:1  |
| endurance test tool              | 1000 cycles of spreading and pulling while the tool is loaded and 1000 cycles of biting in material that cannot be cut |
| endurance test dead man's handle | 6000 cycles  |

| Standard supplied with  |  |
|---|--|
| <ul style="list-style-type: none"> <li>Carrying handle with integrated lighting</li> <li>i-Bolt Technology</li> </ul> |  |

| Accessories                           |             |
|---------------------------------------|-------------|
| Pulling Adapter Set W/Hooks 3150/4150 | 158.582.004 |
| Pulling Chain Set With Hooks 3/8"     | 158.582.001 |

