## **Technical specification sheet**



## 4240 CORE | Spreader

Specifications		
article number		158.012.101
model		4240 CORE
equipped with (connector type)		CORE
short description		Spreader
max. working pressure	psi	10443
spreading distance	in	27
pulling distance	in	18.3
max. spreading force	lbf	33625
min. spreading force (EN 13204)	lbf	9667
max. squeezing force	lbf	14613
weight, ready for use	lb	41.5
dimensions (LxWxH)	in	30.4 x 11.7 x 8.1
temperature range	°F	-4 + 131
UL listed		yes
NFPA 1936, HPF	lbf	12170
NFPA 1936, HSF	lbf	13184
NFPA 1936, LPF	lbf	5400
NFPA 1936, LSF	lbf	8476
NFPA 1936 compliant		yes

holmatro outer formation of the control of the cont
--

Safety factors / tests	
hydraulic safety factor	2:1
endurance test tool	1000 cycles of spreading and pulling while the tool is loaded
endurance test dead man's handle	6000 cycles

## Standard supplied with

- Built-in Speed Valve
  Carrying handle with integrated lighting

Accessories	
Spreading Tip, SP 4240/3240	150.013.702
Cutting Tip, SP 4240/3240	150.013.703
Pulling Chain Set With Hooks 3/8"	158.582.001
Pulling Attachments Set 4240	158.582.008





## holmatro.com